



SPECIFICATIONS	PF-65-100	
Flow Range	1965-3930 GPM	
System Inlet Connection	10" Flg	
System Outlet Connection	10" Flg	
Purge Connection	2" fpt	
Manual Air Bleed Valve	1/4" fpt	
Volume	98 GAL	
Est. Weight, Dry	1056 lbs	
Est. Weight, Operating	1870 lbs	
Handhole - Inspection/Cleanout	4" x 6"	

## **ENGINEERING • MANUFACTURING • SERVICE**

# PF-65-100 SPECIFICATION SHEET FLANGED SEPARATOR

### Features:

- True tangential entry
- 150 psi working pressure
- Five year limited warranty
- Electrically actuated ball valve
- 22 1/2° Profile vessel

## **Options:**

- Automatic purge
- Isolation valve kit
- Wall mounting brackets/legs
- Inspection port

## **SYSTEM COMPONENTS**

#### Separator:

- Carbon steel construction
- Fusion-bond polyester coated vessel
- Manual air bleed valve
- Inlet/Outlet pressure gauges

#### **Electrical Controls:**

- NEMA 4X Enclosure
- Short circuit protection
- Purge switch selector
- Adjustable purge timer

PRESSURE DROP vs. FLOW RATE								
Pressure Drop	3 psi	4 psi	6 psi	8 psi	10 psi	12 psi	CV Factor	
Flow (GPM)	1965	2269	2779	3902	3587	3930	1134.4	

<sup>\*(</sup>Flow rate / CV values may vary slightly

To determine the approximate pressure drop at flow rates not shown in this chart, use the following formula  $\Delta P$ = (FLOW RATE / CV) $^2$ 

CV Factor: CV is defined as the flow in gallons per minute (GPM) that will produce a one pound pressure drop across the separator

